



Specified Fittings, LLC

164 West Smith Road • PO Box 28157 • Bellingham, WA 98228-0157 | Email: sales@specfit.com

Bellingham: 360-398-7700 | 360-398-7051 Fax
Stevensville: 406-777-3466 | 406-777-7181 Fax
Mexico (Toll Free): 800-429-1705 | 800-574-1075 Fax

Specified Fittings fabricates duct fittings using the following materials:

SPECIFICATIONS

PVC Duct

All exhaust duct piping, size 6" through 24", shall be PVC seamless extruded type, as manufactured by Harvel Plastics Inc. This duct pipe shall be extruded from a Type I, Grade I Polyvinyl Chloride (PVC) compound with a Cell Classification of 12454 per ASTM D1784. All extruded duct pipe shall meet Harvel Plastics Inc. published standards with regard to material and dimensions, and shall carry a maximum temperature rating of 140°F. All extruded duct pipe shall be manufactured in the USA, using domestic materials, by an ISO 9001-certified manufacturer, and shall be stored indoors at the manufacturing site until shipped from the factory. All extruded PVC duct pipe shall be marked with the manufacturer's name or identifying symbol.

SPECIFICATIONS

CPVC Duct

All exhaust duct piping, sizes 6" through 24", shall be CPVC seamless extruded type, as manufactured by Harvel Plastics, Inc. This duct pipe shall be extruded from Chlorinated Polyvinyl Chloride (CPVC) compound with a Cell Classification of 23437 per ASTM D1784; trade name CPVC. All extruded duct pipe shall meet Harvel Plastics, Inc. published standards with regard to material and dimensions, and shall carry a maximum temperature rating of 200°F. All extruded duct pipe shall be manufactured in the USA, using domestic materials, by an ISO 9001 certified manufacturer, and shall be stored indoors at the manufacturing site until shipped from the factory. All extruded CPVC duct pipe shall be marked with the manufacturer's name or identifying symbol, and the CPVC material trademark.