



SPECIFIED FITTINGS, LLC

164 W. SMITH RD
 BELLINGHAM, WA 98226
 888-734-8846 (T)
 888-734-8258 (F)
spec@specfit.com

483 STEVENSVILLE AIRPORT RD.
 STEVENSVILLE, MT 59870
 406-777-3466 (T)
 406-777-7181 (F)
sales@specfit.com

www.specfit.com

SIZE	OD	A	PRESSURE	
			CLASS	PART #
6"	6.625	9.25	150	HD1916FM150
6"	6.625	9.25	200	HD1916FM200
8"	8.625	9.25	150	HD1918FM150
8"	8.625	9.75	200	HD1918FM200
10"	10.75	9.5	150	HD19110FM150
10"	10.75	10.5	200	HD19110FM200
12"	12.75	11	150	HD19112FM150
12"	12.75	12	200	HD19112FM200
14"	14	12	150	HD19114FM150
14"	14	12	200	HD19114FM200
16"	16	12	150	HD19116FM150
16"	16	12	200	HD19116FM200
18"	18	13	150	HD19118FM150
18"	18	13	200	HD19118FM200
20"	20	13	150	HD19120FM150
20"	20	13	200	HD19120FM200
24"	24	13	150	HD19124FM150
24"	24	20	200	HD19124FM200
26"	26	25.75	150	HD19126FM150
26"	26	25.75	200	HD19126FM200



Description: IPS HDPE FABRICATED CAP WITH PUP PLAIN-ENDS
 Material: HDPE
 Size: 6" -26"
 CLASS 150, CLASS 200
 PSI RATINGS 150, 200

NOTE:

Fittings are manufactured and tested to the requirements of ASTM D3035, D3261, AWWA C901 or C906, and FM 1613. These fittings are tested to the requirements of ASTM D3261 and are compatible for heat fusion with any pipe and or fitting of compatible resin. Made from PE3408/3608 or PE4710 material. All raw material shall comply with NSF-61. Other OD's, SDR's and Pressure Ratings available upon request. Per FM 1613 and AWWA C906, the working pressure rating equals the pressure class with an allowance included in the WPR for pressure surge.

FOR DISCLAIMER REFER TO FM DIMENSION CATALOG.