



Specified Fittings, LLC

164 West Smith Road • PO Box 28157 • Bellingham, WA 98228-0157

Bellingham: 360-398-7700 | 360-398-7051 Fax
Stevensville: 406-777-3466 | 406-777-7181 Fax
Mexico (Toll Free): 800-429-1705 | 800-574-1075 Fax

September 17 2010

To Whom It May Concern:

This letter is regards the use of fiberglass overlay as a structural reinforcement on fabricated PVC fittings. The use of reinforcement to achieve required pressure ratings is not disallowed by industry standards and specifications, and the use of fiberglass overlay is common and accepted industry practice. Indeed, to the best of our knowledge, every manufacturer of fabricated pressure fittings in the U.S. will use such reinforcement. Fittings designed for use at elevated pressures may be reinforced where reinforcement has been deemed necessary for proper fitting performance. Further, each fitting that receives such reinforcement will undergo the Quality Assurance process in place at Specified Fittings, and will be found acceptable as per ASTM D2563, and shall be free of visible chips, cracks, foreign inclusions, air bubbles, lack of fill-out, delamination and sharp obtrusive surfaces as defined in that standard.

If you have any other questions or concerns, please get back in touch with us.

Sincerely,
Brad Sukolsky,
Specified Fittings